

proxSafe®

Key Management & Smart Storage Systems

The intelligent management system for keys and equipment with comprehensive audit and reporting capabilities. Control who can have access to individual items and restrict when they can be taken. Keys, radios, test equipment, tools, laptops and much more can now be managed efficiently with increased accountability so you know where they are and who has them. The powerful software Commander Connect allows easy configuration and control of access rights, time profiles and the creation of individual reports. That way you stay in control at all times and make the best use of your equipment.



Powerful, with graphical user interface

The proxSafe C6 Touch Terminal combines the simple and intelligent operation of the proxSafe terminal with the display and operating functions of a 5.7" color touch panel with capacitive touch screen. This allows the C 6 to provide a user interface similar to a smart phone.

The touch terminal C 6 is compatible with all key management systems as well as drawers and compartment systems from the proxSafe family. It comes with an administrator ID card to set up the system. Users can identify themselves via a proximity card or entering a PIN. At the terminal, the user selects the desired key using the integrated keypad. The proxSafe system guides the user to the appropriate slot. The period of access authorization, the duration of withdrawal and the maximum number of removable keys can be set individually for each user.

The proxSafe terminal C 1 allows for quick return of the keys. The user only has to present the keyTag in front of the terminal. The terminal will immediately open the key cabinet and guide the user to the correct proxCylinder. The optional available multi-technology reader allows the use of many existing access control cards for user identification. Nearly all features of the proxSafe system can be executed by the Terminal without the need for a PC connection.

Alternatively, the data stored in the terminal can be continuously synchronized with those of the central database for network operation. Even in case of a power failure the power management of the terminal ensures that the proxSafe system keeps working as long as possible.

Your benefits at a glance:

- **Comfortable to use via 5.7" touch display**
- **Multi-Technology reader for user identification**
- **Quick key return via 125 kHz reader**
- **Network and stand-alone capable**
- **Supports UNICODE**

Technical Data

Dimensions WxHxD:	145 x 230 x 92 mm
Housing Material:	ASA, ALUMINIUM
Color:	black
Protection Class:	IP54
Operating Temperature:	+5 ... +50 °C
Relative Humidity:	5...95 %, non-condensing
Display:	5.7" color display
Screen Resolution:	480 x 640
Operation:	capacitive touch screen
Smart Card:	integrated SD smart card
Languages:	various languages selectable
Reader (Option):	Quick key return and user-ID <ul style="list-style-type: none"> • Reader Module 125 kHz • 13,56 MHz MIFARE DESFire and 125 kHz • 13,56 MHz LEGIC® and 125 kHz • 13,56 MHz I-Class™ and 125 kHz • 13,56 MHz FeliCa and 125 kHz
Database:	4096 keyTags 8192 users 14000 events